




## Brighton Spec Sheet



ALL DESIGNS ARE V-GROOVE AS STANDARD. SQUARE, CHAMFER OR U-GROOVE OPTIONS ARE AVAILABLE ON REQUEST.

6 x 3mm V-GROOVE DETAIL



**Door Weights - kg/m<sup>2</sup>**

Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0

### Brighton Grooving Dimensions (mm)

Side Stile Width and Number	
1980	110 x 1
2200	110 x 1
2400	110 x 1
2550	110 x 1
2700	110 x 1
<b>Brighton Top Rail</b>	110
<b>Brighton Mid Rails</b>	110
<b>Brighton Bottom Rail</b>	110

Core Availability	Available Finishes			Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide				
	Hollow	Polystyrene	Solid	Un-Primed	U.V. Primed	Rails	Stiles	Lockblocks
1980 High	•	•	•	MTO	Ex-Stock (38mm H/C & S/C)	Ex 35mm	Ex 35mm	400 x 70mm
Up to 2400 High	•	•	•	MTO	Ex-Stock (38mm H/C & S/C)	Ex 140mm	Ex 35mm	800 x 70mm
2700 High	•	•	•	MTO	MTO	Ex 35mm	Ex 35mm	400/800 x 70mm
Oversize	N/A	•	N/A	MTO	N/A	Ex 140mm	Ex 35mm	N/A
						Ex 105mm	Ex 105mm	N/A
						Ex 105mm	Ex 105mm	N/A

### Skin and Thickness Options (MDF Skins)

	34.5mm	37mm	38mm	39.5mm	42mm
<b>Hollow</b>	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
<b>Polystyrene</b>	4.75mm Skin	6.0mm Skin	4.75mm Skin	4.75mm Skin	6.0mm Skin
<b>Solid</b>	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
<b>Oversize</b>	N/A	6.0mm Skin	N/A	N/A	6.0mm Skin

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high

- All hollow and polystyrene doors have double lock blocks
- Stock doors are standard sizes between 410mm and 910mm wide

- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options