





Cashmere Spec Sheet



ALL DESIGNS ARE V-GROOVE AS STANDARD. SQUARE, CHAMFER OR U-GROOVE OPTIONS ARE AVAILABLE ON REQUEST.

6 x 3mm V-GROOVE DETAIL



Door Weights - kg/m²

Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0

Cashmere Grooving Dimensions (mm)

	Side Stile Width and Number	Mid Stile Width and Number
410	110 x 2	95.00 x 2
460	110 x 2	80.00 x 3
510	110 x 2	96.66 x 3
560	110 x 2	85.00 x 4
610	110 x 2	97.50 x 4
660	110 x 2	88.00 x 5
710	110 x 2	98.00 x 5
760	110 x 2	90.00 x 6
810	110 x 2	98.33 x 6
860	110 x 2	91.40 x 7
910	110 x 2	98.57 x 7
960	110 x 2	92.50 x 8
1010	110 x 2	98.75 x 8
1060	110 x 2	93.33 x 9
1110	110 x 2	98.88 x 9
1160	110 x 2	94.00 x 10
1210	110 x 2	99.00 x 10
Cashmere Top Rail		110
Cashmere Bottom Rail		180

Core Availability	Available Finishes			Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide				
	Hollow	Polystyrene	Solid	Un-Primed	U.V. Primed	Rails	Stiles	Lockblocks
1980 High	•	•	•	MTO	Ex-Stock (38mm H/C & S/C)	Ex 35mm	Ex 35mm	400 x 70mm
Up to 2400 High	•	•	•	MTO	Ex-Stock (38mm H/C & S/C)	Ex 140mm	Ex 35mm	800 x 70mm
2700 High	•	•	•	MTO	MTO	Ex 35mm	Ex 35mm	400/800 x 70mm
Upsize	N/A	•	N/A	MTO	N/A	Ex 140mm	Ex 35mm	N/A
						Ex 105mm	Ex 105mm	N/A
						Ex 105mm	Ex 105mm	N/A

Skin and Thickness Options (MDF Skins)					
	34.5mm	37mm	38mm	39.5mm	42mm
Hollow	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Polystyrene	4.75mm Skin	6.0mm Skin	4.75mm Skin	4.75mm Skin	6.0mm Skin
Solid	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Upsize	N/A	6.0mm Skin	N/A	N/A	6.0mm Skin

- All doors over 1210 wide supplied un-primed
- 'Upsize' is doors over 1210mm wide or 2700mm high
- All hollow and polystyrene doors have double lock blocks
- Stock doors are standard sizes between 410mm and 910mm wide
- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options