



## MDF Flush Panel Spec Sheet



### Door Weights - kg/m<sup>2</sup>

Door Weights - kg/m <sup>2</sup>	
Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0

### Available Finishes

	Un-Primed	U.V. Primed
1980 High	MTO	Ex-Stock
Up to 2400 High	MTO	Ex-Stock
2700 High	MTO	MTO
Oversize	MTO	N/A

### Core Availability

	Hollow	Polystyrene	Solid
1980 High	Ex-Stock	MTO	Ex-Stock
Up to 2400 High	Ex-Stock	MTO	Ex-Stock
2700 High	MTO	MTO	MTO
Oversize	N/A	•	N/A

### Skin and Thickness Options (MDF Skins)

	34.5mm	37mm	38mm	39.5mm	42mm
Hollow	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Polystyrene	4.75mm Skin	6.0mm Skin	4.75mm Skin	4.75mm Skin	6.0mm Skin
Solid	N/A	N/A	4.75mm Skin	4.75mm Skin	6.0mm Skin
Oversize	N/A	6.0mm Skin	N/A	N/A	6.0mm Skin

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high
- All hollow and polystyrene doors have double lock blocks
- Stock doors are standard sizes between 410mm and 910mm wide
- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options