

Veneer Collection

Available from



Eucalyptus Oak (Tasmanian Oak)



ALL DOORS ARE AVAILABLE IN HOLLOWCORE, SOLIDCORE, POLYSTYRENE CORE. ALL DOORS ARE AVAILABLE UP TO 2700MM HIGH. OTHER VENEER OPTIONS ARE AVAILABLE ON REQUEST.

Door Weights - kg/m2
Hollow 10.5
Polystyrene 10.5
Solid 28.5
Steel per L/M 2.0

Tasmanian Oak				
Description	Pale light brown colour with green - grey streaks. Mainly consistent in colour but can include pinker toning			
Veneer Features	Small gun vein lines and pips permissible			
Veneer Cuts Available	Quarter Cut			
Standard Matching Pattern	Slip matched			
Country of Origin	Australia, New Zealand, Spain			
Sustainably Harvested	Yes			
Veneer Hardness	Hardwood			

Core Availability						
	Hollow	Polystyrene	Solid			
1980 High	•	•	•			
2400 High	•	•	•			
2700 High	•	•	•			
Oversize	N/A	•	N/A			

Door Frame and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide					
	Rails	Stiles	Lockblocks		
Hollow	Ex 35mm	Ex 35mm	400 x 70mm*		
Polystyrene	Ex 35mm	Ex 35mm	400 x 70mm*		
Solid	Ex 35mm	Ex 35mm	N/A		
960mm Wide +	Ex 105mm	Ex 105mm	N/A		
>2400mm High	Ex 105mm	Ex 105mm	N/A		

Skin and Thickness Options					
	36mm	39mm	42mm		
Hollow	4.75mm Skin	4.75mm Skin	6.0mm Skin		
Polystyrene	4.75mm Skin	4.75mm Skin	6.0mm Skin		
Solid	4.75mm Skin	4.75mm Skin	6.0mm Skin		
Oversize		6.0mm Skin, option of 38 or 43mm			

- 'Oversize' is doors over 1210mm wide or 2700mm high
- All veneer doors are made to order

 All hollow and polystyrene doors have double lock blocks, 400mm long for 1980 doors, and 800mm long for overheight doors