



Sapele (Quarter Cut) Spec Sheet



ALL DOORS ARE AVAILABLE IN HOLLOWCORE, SOLIDCORE, POLYSTYRENE CORE. ALL DOORS ARE AVAILABLE UP TO 2700MM HIGH. OTHER VENEER OPTIONS ARE AVAILABLE ON REQUEST.

Door Weights - kg/m²

| | |
|---------------|------|
| Hollow | 10.5 |
| Polystyrene | 10.5 |
| Solid | 28.5 |
| Steel per L/M | 2.0 |

Sapele Quarter

| | |
|----------------------------------|---|
| Description | Browny red colouring, dominant grain and obvious vertical grain lines |
| Veneer Features | Consistent colour very few defects or pips. |
| Veneer Cuts Available | Quarter Cut |
| Standard Matching Pattern | Book Matched, Matching pairs available |
| Country of Origin | East/West Africa |
| Sustainably Harvested | Yes |
| Veneer Hardness | Hardwood |

Core Availability

| | Hollow | Polystyrene | Solid |
|-----------|--------|-------------|-------|
| 1980 High | • | • | • |
| 2400 High | • | • | • |
| 2700 High | • | • | • |
| Oversize | N/A | • | N/A |

Door Frame and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide

| | Rails | Stiles | Lockblocks |
|--------------|----------|----------|-------------|
| Hollow | Ex 35mm | Ex 35mm | 400 x 70mm* |
| Polystyrene | Ex 35mm | Ex 35mm | 400 x 70mm* |
| Solid | Ex 35mm | Ex 35mm | N/A |
| 960mm Wide + | Ex 105mm | Ex 105mm | N/A |
| >2400mm High | Ex 105mm | Ex 105mm | N/A |

Skin and Thickness Options

| | 36mm | 39mm | 42mm |
|-------------|----------------------------------|-------------|------------|
| Hollow | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Polystyrene | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Solid | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Oversize | 6.0mm Skin, option of 38 or 43mm | | |

- 'Oversize' is doors over 1210mm wide or 2700mm high
- All veneer doors are made to order

- * All hollow and polystyrene doors have double lock blocks, 400mm long for 1980 doors, and 800mm long for overheight doors